


Features:

- Two-way passive high SPL loudspeaker
- Solid 20mm Birch Multi-ply construction
- Steel powder coated grill (dent resistant)
- Cast aluminum frame 12" woofer
- 4 inch edge wound copper clad aluminum voice coil
- High power phase corrected compression horn
- Titanium diaphragm
- Rotate-able horn flange for horizontal mounting
- Audiophile grade internal crossover or active crossover (switchable bi-amp-able)
- High frequency protection circuit
- Steel 1-3/8 pole mount flange 5
- Optional 3 x M-10 fly bolts
- Tough coat painted finish



Specifications:

- Power rating 500W RMS 1000W Peak
- Freq response 50Hz- 20kHz
- Sensitivity 94dB 1W/1M
- Impedance 8 ohms (nominal)
- Crossover 1.4kHz (or switchable to active bi-amp)

LF:

- 12" cast aluminum frame
- 4" edge wound copper/aluminum voice coil

HF:

- 3" Phase corrected Titanium compression driver
- Dispersion 80 x 60 (rotate-able horn for horizontal mounting)
- Max SPL 122dB
- Connectors Dual Speakon 4 pin bi-amp or pass through
- 14 M-10 fly points
- Steel pole mount flange 1-3/8
- Side handle and rubber feet included

Dimensions:

(W) x14.9"/380mm (H) x 25.98"/660mm (D) x 14.4" 367mm

Weight: 34kg/74 lbs



Optional 3 x M-10 fly bolts

Cast frame 500W 12 driver 4"VC

